


01. Tubes de précision · Tubos de precisión

Tubes carrés

Tubo cuadrado



Acier laminé à chaud · Acero laminado en caliente



 Poids théorique kg / mètre
 Peso teórico kg / metro

Longueur de côté spécifié Longitud de lado especificado			Épaisseur t en mm / Espesor t en mm				
H	B	Tolérance sur H et B Tolerancia sobre H y B	1,5	2	2,5	3	4
14	14	±0,20	0,585	0,747			
16	16	±0,20	0,679	0,872			
18	18	±0,20	0,773	0,998			
20	20	±0,20	0,868	1,124			
25	25	±0,25	1,103	1,438			
30	30	±0,25	1,339	1,752	2,148	2,360	
35	35	±0,25	1,574	2,066	2,541	2,830	
40	40	±0,30	1,810	2,380	2,933	3,300	4,200
45	45	±0,30	2,045	2,694	3,326	3,770	4,830
50	50	±0,30	2,281	3,008	3,718	4,250	5,450
60	60	±0,35	2,752	3,636	4,503	5,190	6,710
70	70	±0,40		4,264	5,288	6,130	7,970
80	80	±0,50		4,892	6,073	7,070	9,220
90	90	±0,60		5,520	6,858	8,010	10,480
100	100	±0,65		6,148	7,643	8,960	11,730

Tubes carrés Tubo cuadrado



Acier laminé à froid · Acero laminado en frío



Poids théorique kg / mètre
Peso teórico kg / metro

Longueur de côté spécifié Longitud de lado especificado			Épaisseur t en mm / Espesor t en mm				
H	B	Tolérance sur H et B Tolerancia sobre H y B	0.8	1	1.2	1.5	2
14	14	±0,20	0.331	0.407	0.480	0.585	0.747
15	15		0.356	0.438	0.518	0.632	0.81
16	16		0.381	0.469	0.555	0.679	0.872
18	18		0.431	0.532	0.631	0.773	0.998
20	20		0.481	0.595	0.706	0.868	1.124
25	25	±0,25	0.607	0.752	0.894	1.103	1.438
28	28		0.682	0.846	1.007	1.244	1.626
30	30		0.732	0.909	1.083	1.339	1.752
32	32		0.783	0.972	1.158	1.433	1.877
35	35		0.858	1.066	1.271	1.574	2.066
40	40	±0,30	0.984	1.223	1.460	1.810	2.380
45	45		1.109	1.380	1.648	2.045	2.694
50	50		1.235	1.537	1.836	2.281	3.008