



Tubes rectangulaires

Tubo rectangular



Acier laminé à chaud · Acero laminado en caliente



Poids théorique kg / mètre
Peso teórico kg / metro

Longueur de côté spécifié Longitud de lado especificado			Épaisseur t en mm / Espesor t en mm				
H	B	Tolérance sur H et B Tolerancia sobre H y B	1,5	2	2,5	3	4
20	10	±0,20	0,632	0,810			
20	15		0,750	0,967			
25	10	±0,25	0,750	0,967			
25	15		0,868	1,124			
30	10	±0,25	0,868	1,124			
30	15		0,985	1,281			
30	20		1,103	1,438			
35	15	±0,25	1,103	1,438	1,756	1,921	
35	20		1,221	1,595	1,952		
35	25		1,339	1,752	2,148	2,360	
40	10	±0,30	1,103	1,438	1,756		
40	15		1,221	1,595	1,952		
40	20		1,339	1,752	2,148	2,360	
40	25		1,456	1,909	2,344	2,600	
40	27		1,503	1,971	2,423	2,691	
40	30		1,574	2,066	2,541	2,830	
40	35		1,692	2,223	2,377	3,098	
45	10		1,221	1,595	1,952	2,156	
45	15		1,339	1,752	2,148		
45	20		1,456	1,909	2,344	2,627	
45	25		1,574	2,066	2,541	2,830	
45	30		1,692	2,223	2,737	3,098	
45	35		1,810	2,380	2,933	3,300	



01. Tubes de précision · Tubos de precisión

Tubes rectangulaires

Tubo rectangular



Acier laminé à chaud · Acero laminado en caliente



Poids théorique kg / mètre
Peso teórico kg / metro


Longueur de côté spécifié Longitud de lado especificado			Épaisseur t en mm / Espesor t en mm				
H	B	Tolérance sur H et B Tolerancia sobre H y B	1,5	2	2,5	3	4
50	10	±0,30	1,339	1,752	2,150	2,360	
50	15		1,456	1,909	2,340	2,627	
50	20		1,574	2,066	2,540	2,830	
50	25		1,692	2,223	2,740	3,098	
50	30		1,810	2,380	2,930	3,300	4,200
50	40		2,045	2,694	3,330	3,770	4,830
60	10	±0,35	1,574	2,066	2,541	2,863	
60	15		1,692	2,223	2,737	3,098	
60	20		1,810	2,380	2,933	3,300	4,200
60	30		2,045	2,694	3,326	3,770	4,830
60	40		2,281	3,008	3,718	4,250	5,450
60	50		2,516	3,322	4,111	4,720	6,080
70	20	±0,40	2,045	2,694	3,326	3,770	4,830
70	30		2,281	3,008	3,718	4,250	5,450
70	40		2,516	3,322	4,111	4,720	6,080
80	20	±0,50	2,281	3,008	3,718	4,250	5,450
80	30		2,516	3,332	4,111	4,720	6,080
80	40		2,752	3,636	4,503	5,190	6,710
80	50		2,987	3,950	4,896	5,660	7,340
80	60		3,223	4,264	5,288	6,130	7,970
90	30		2,752	3,636	4,503	5,190	6,710
90	40		2,987	3,950	4,896	5,660	7,340
90	50		3,223	4,264	5,288	6,130	7,970

Tubes rectangulaires

Tubo rectangular



Acier laminé à chaud · Acero laminado en caliente



Poids théorique kg / mètre
Peso teórico kg / metro

Longueur de côté spécifié Longitud de lado especificado			Épaisseur t en mm / Espesor t en mm				
H	B	Tolérance sur H et B Tolerancia sobre H y B	1,5	2	2,5	3	4
100	20	±0,65	2,752	3,636	4,503	5,190	6,710
100	30		2,987	3,950	4,896	5,660	7,340
100	40		3,223	4,264	5,288	6,130	7,770
100	50		3,458	4,578	5,681	6,600	8,590
100	60			4,892	6,073	7,070	9,220
100	80			5,520	6,858	8,010	10,480
120	40	±0,70		4,892	6,073	7,070	9,220
120	60			5,520	6,858	8,010	10,480


01. Tubes de précision · Tubos de precisión

Tubes rectangulaires

Tubo rectangular



Acier laminé à froid · Acero laminado en frío


 Poids théorique kg / mètre
 Peso teórico kg / metro

Longueur de côté spécifié Longitud de lado especificado			Épaisseur t en mm / Espesor t en mm				
H	B	Tolérance sur H et B Tolerancia sobre H y B	0.8	1	1.2	1.5	2
20	10	±0,20	0.356	0.438	0.518	0.632	0.810
20	15		0.418	0.516	0.612	0.750	0.967
25	10	±0,25	0.418	0.516	0.612	0.750	0.967
25	15		0.481	0.595	0.706	0.868	1.124
25	20		0.544	0.673	0.800	0.985	1.281
30	10	±0,25	0.481	0.595	0.706	0.868	1.124
30	15		0.544	0.673	0.800	0.985	1.281
30	20		0.607	0.752	0.894	1.103	1.438
30	25		0.670	0.830	0.989	1.221	1.595
35	10	±0,25	0.544	0.673	0.800	0.985	1.281
35	15		0.607	0.752	0.894	1.103	1.438
35	20		0.670	0.830	0.989	1.221	1.595
35	25		0.732	0.909	1.083	1.339	1.752
40	10	±0,30	0.607	0.752	0.894	1.103	1.438
40	15		0.670	0.830	0.989	1.221	1.595
40	20		0.732	0.909	1.083	1.339	1.752
40	25		0.795	0.987	1.177	1.456	1.909
40	30		0.858	1.066	1.271	1.574	2.066
40	35		0.921	1.144	1.365	1.692	2.223
50	10	±0,30	0.732	0.909	1.083	1.339	1.752
50	15		0.795	0.987	1.177	1.456	1.909