


03. Tubo galvanizado sendzimir · Sendzimir galvanized tubes


Tubo redondo
Circular tube



Peso teórico kg / metro
Theoretical weight kg / meter

Diámetro exterior especificado D con intervalos de tolerancia Specified outside diameter D with tolerance intervals		Espesor de pared t / t wall thickness		
		1,20	1,5	2
16	±0,12	0,438	0,536	0,690
18		0,497	0,610	0,789
19		0,527	0,647	0,838
20	±0,15	0,556	0,684	0,887
22		0,615	0,758	0,986
25		0,704	0,869	1,134
28		0,793	0,980	1,282
30		0,852	1,054	1,380
32	±0,20	0,911	1,128	1,479
35		1,000	1,239	1,627
38		1,089	1,350	1,775
40		1,148	1,424	1,873
42		1,207	1,497	1,972
42,4		1,230	1,513	1,992
44	±0,25	1,266	1,572	2,071
45		1,296	1,608	2,120
48,3		1,390	1,719	2,366
50		1,444	1,793	2,366
51		1,473	1,831	2,416
55	±0,30	1,592	1,978	2,613
57		1,651	2,052	2,712
60		1,740	2,163	2,859
63,5			2,293	3,033
70	±0,35		2,533	3,352
75			2,718	3,599
76			2,755	3,648

Tubo redondo Circular tube



Peso teórico kg / metro
Theoretical weight kg / meter

Diámetro exterior especificado D con intervalos de tolerancia Specified outside diameter D with tolerance intervals	Espesor de pared t / t wall thickness		
	1,20	1,5	2
80 ±0,40		2,903	3,845
89		3,235	4,289
90		3,272	4,338
100 ±0,50		3,642	4,831
101,6			4,912
108 ±0,60			5,226
114			5,538
120			5,817
125			6,064
127 ±0,80			6,163
133			6,458
139,7			6,840
159 ±1			7,740